




TECHNICAL DATA SHEET

FOR PROFESSIONAL USE ONLY	
TDS CODE: TCP400 B-G-A- V12025	
PRODUCTS	
PLASTIC PRIMER 400ml Spray	
PRODUCT DESCRIPTION	
<p>Description</p> <ul style="list-style-type: none">Plastic Primer / Adhesion Promotor is a specially formulated transparent advanced fast drying primer for plastics, plastic trim and plastic bumpers which both seals plastic surfaces and ensures a strong foundation for the next layer of primer or paint. Specially developed to prepare all plastic surfaces for priming and painting and promotes optimum adhesion to plastics. Helps to reduce runs and distortions in the main paintwork, giving a smoother finish to the paint applicationTranslucentFast dryingCreate a stable base for colour coat.Fast DryingUse in conjunction with TeqPro Plastic Paints	
	
COLOURS: Clear	
GLOSS GRADE: N/A	

VOLATILE ORGANIC COMPOUNDS
<ul style="list-style-type: none"> Plastic Primer VOC = 700g/l VOC less than 850 g/l. This complies with the EU directive 2004/42/II5(e) that sets the VOC values for this product category (IIB), as less than 840g/l.

	APPLICATION PROCESS		DRYING TIMES
	<ul style="list-style-type: none"> Before use, carefully read the directions on the packaging and act accordingly. Always wear the correct PPE. Mask, Gloves and Eyewear Pre-Treatment: The surface must be clean, dry and completely free of grease, dust, polish and any other contaminants. Surface can be sanded with P600 prior to application. For final degreasing we recommend using TeqPro GWD1 Surface Degreasing Wipes. Application: The aerosol should be at room temperature. Best processing temperature 10 to 25°C. Before use, shake can for 2 minutes until all the shake balls can be heard moving freely inside the can and then spray a sample. Adjust the fan Spray nozzle to the desired spray pattern and note the distance to the surface to be sprayed which is approximately 25 to 30 cm. Apply the Plastic Primer in two thin layers rather than in one heavy coat. Before applying the next layer, shake the aerosol again. After use, clean the valve (turn the aerosol upside down and press the nozzle for approximately 5 seconds). Drying time will depend on the ambient temperature, the humidity of the air and the thickness of the paint applied. 		<p>Drying times</p> <p>Drying time will depend on the ambient temperature, the humidity of the air and the thickness of the paint applied.</p>

FURTHER INFORMATION

Caution

- Store this product in dry cool places, away from fire and other heat sources.
- Store out of direct sunlight.
- Pressurized container, do not pierce, burn or expose to temperatures exceeding
- Keep out of reach of children
- Do not breathe vapour. Wear suitable PPE, eye protection and mask.
- Dispose in accordance with environmental health regulations

LEGAL INFORMATION

TeqPro Warranty Information

Important Notice to prospective purchaser: TeqPro make no warranties either express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The end user or person using the product is responsible for determining whether the TeqPro product is fit for the particular purpose and suitable for individual user's application. Many different factors can affect the use and performance of a TeqPro product for a particular application. The material, surface or substrate to be painted, filled or bonded with the particular product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a TeqPro product, some of which are uniquely within the user's control and knowledge. It is essential that the end user evaluates the TeqPro product to determine whether it is fit for a particular purpose and suitable for user's individual methods of application.

Limitation of Remedies and Liability: If the TeqPro product is proved to be defective, the exclusive option at Teqpro's discretion shall be to refund the purchase price or to repair and replace the defective TeqPro product. TeqPro shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

The information contained in the TDS is up-to-date and correct on the day the information is released.

Because TeqPro cannot control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TeqPro shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Under no circumstances shall TeqPro be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damage, including loss of profits resulting from the use of products manufactured by TeqPro and / or TeqPro's services

